

Product Technical Information Sheet for: Room Air Conditioner (Voluntary Scheme)

產品技術資料表:空調機(自願性計劃)

(Please reproduce this page as needed, in case of more than one model) (如申請產品型號超過一款,請複製本頁以應所需)

(1)	Brand : 品牌:												
(2)	Model: 型號:												
(3)	Country of Origin: 原產地:												
(4)	Appliance Category: 器具類別:		1	2		□ 3		□ 4					
		T							1				
(5)	Information on Energy Label 能源標籤資 料				Cooling (制冷)					Heating (供暖)			
		Annual Er Consump 每年的能 瓦小時):	(specify as an integer)(以整數表示)				(specify as an integer) (以整數表示)						
		Cooling and Heating Capacity (kW): 製冷及供暖量(千瓦):		(to 2 decimal places) (二個小數位)					(to 2 decimal places) (二個小數位)				
		Energy Efficiency Grade: 能源效益級別:		1	2	- 3		5	1	2	3	4	- 5
		Refrigerar 製冷劑:						<u> </u>			<u> </u>		
l													
(6)			Rated	Value 額定值			١	alue 量	lue 量度值				
			Cooling (制冷)		Heating (供暖)			Cooling (制冷)			Heating (供暖)		
	Cooling and Heating Capacity (kW): 製冷及供暖量(千瓦):												
	Power consumption (kW): 功率消耗量(千瓦):												
	Half / Minimum* cooling and heating capacity (kW) (note1): 一半 / 最小* 製冷及供 暖量 (千瓦) (註 1):												

Note 註:

- 1. Only applicable to room air conditioners with two-stage capacity, multi-stage capacity and continuously variable capacity.
- 1. 只適用於兩重階段輸出、多重階段輸出及可持續變換輸出空調機。
- * Delete as appropriate (删除不適用者)

	Rated Value 額定值				Measured Value 量度值					
	Cooling	(制冷)	Heatin	ıg (供暖)	Cooling	(制冷)	Heati	Heating (供暖)		
Half / Minimum* power consumption (kW) (note1): 一半 / 最小* 功率消耗 量 (千瓦) (註 1):										
Cooling and heating seasonal performance factors (to 3 decimal places): 製冷及供暖季節性表現系數(三個小數位):										
	Cooling (製冷)				Heating (供暖)					
Maximum cooling and heating tests 最大運行製冷及供暖 測試:	pass 合格 ロ		fail 不	合格□	pass ∉	済格□	fail 不	fail 不合格 ロ		
Type of compressor <u>壓</u> 縮機類別:	fixed capacity 固定 輸出	two-stage capacity 兩重階段 輸出	multi-stage capacity 多重階段 輸出	continuously variable capacity 可變換輸出	fixed capacity 固定 輸出	two-stage capacity 兩重階段 輸出	multi-stage capacity 多重階段 輸出	continuously variable capacity 可變換輸出		
Type of power input 電源性質:	single phase 單相 🗖				three phase 三相 口					
Method of obtaining fixed output at full capacity ^(note 1) : 獲得固定最大輸出的 方法 ^(益 1) :	(□ submit	in separa	te sheet	引加紙提交)	(□ submit	in separa	ite sheet	引加紙提交)		
Method of obtaining fixed output at half / minimum* capacity ^(note 1) : 獲得固定一半 / 最小* 輸出的方法 (註 1):	(□ submit	in separat	e sheet 另	加紙提交)	(□ submit	in separa	ite sheet <i>牙</i>	引加紙提交)		

Note 註:

- 1. Only applicable to room air conditioners with two-stage capacity, multi-stage capacity and continuously variable capacity.
- 1. 只適用於兩重階段輸出、多重階段輸出及可持續變換輸出空調機。

^{*} Delete as appropriate (删除不適用者)